

Jelly Packing Machine JT-400



Applications:

- It is suitable for all kinds of food, frozen food, coffee beans, granulated sugar, pet food, peanut, popcorn, dried fruit, seed, small hardware, seed, and etc.
- For 10-800g/ 20-1500g each bag.
- Applicable film materials: all kinds of complex film, single-layer PE film.

Sample bags:



Products informations:

- English and Chinese screen display, operation is simple.
- Mitsubishi PLC computer system, function is more stable, adjustment any parameters not need stop machine.
- It can stock ten dispose, simple to switchover.
- Panasonic servor motor drawing film, position accurately.
- Horizontal, vertical temperature control, suitable for various of mix film, PE film packing material.
- Packing type diversification, pillow sealing, standing type, punching etc.
- Bag-making, sealing, packing, print date in one operation.

Technical Parameters:

Туре	JT-400
Packing speed	5-60 bags/ min
Display	10.4 inch touch screen
Weigher type	10/14 heads
Weigher hopper volume	1.3L/ 2.5L
Weighing accuracy	±0.5-1.5 g
Single weighing range	10-800g/ 20-1500g
Pillow bag sizes	Bag length 50-250 mm;
	Bag width 50-200 mm
Stand bag size	Bag length 50-250 mm;
	Bag front width 50-120 mm
	Bag side width 40-80 mm
The max. roll film width	420 mm
Type of sealing	Pillow bag, standing up bag
Measuring range	30-1200 ml
Gas consumption	0.3 m³/ min
Air consumption	0.65 mpa
Film pulling driven system	servo motor
Horizontal sealing driven system	cylinder/ servo motor
Power supply specifications	220V 50Hz/ 60Hz 3.7KW
Overall size	990(L)* 1430(W)* 2200(H) mm
Weight of machine	800 kg
Whole machine cover material	304 stainless steel