



OK-150A Single Head Shrink Label Machine (PVC PET Label)



Specifications

Shrink sleeve labeling machine is custom built to meet the exacting demands of manufacturers and suppliers. It can be used stand alone or integrated in-line and matching filling equipment speeds.

It is built upon a framework of seam welded, food grade 304 stainless steel section. This solid foundation keeps movement and vibration to an absolute minimum to ensure consistent, accurate labeling. Unit cutter head plane design in China which apply to the container of $\phi 30$ mm— $\phi 130$ mm. you never need to change or debug it. It also has unique light touch human-machine screen, that means, auto search original location as well as safety and convenience which is ahead of other congener products.

Technical Parameters:

- Model : OK-150A
- Capacity : 1000BPH-24000BPH
- Material : SUS 304 , SUS 316 The diameter of the product: 10-120 mm
- The height of the product: 20-300 mm
- The size of the label: H: 15-150 mm; L: 25-300 mm
- The inside diameter of the roll: 76 mm
- The outside diameter of the roll: 300 mm (maximum)
- Labeling speed: 200-400 bottles/min Error: ± 0.5 (depending on the size of the product)
- Voltage: 220V; 50/60HZ; 1.2KW
- (Main Machine) Packing size : 2100x1250x2200mm Gross Weight: 400Kg
- (Tunnel) Packing size :1900x600x1800mm Gross Weight : 300Kg
- (Steam Generator) Packing size :800X450X1150mm Gross Weight 75Kg