

YB-JG6 Automatic Dishwashing Liquid Laundry Detergent Bottling Machines



This Liquid Filling machine is specially developed for the low viscosity but corrosive liquid filling. The whole machine is controlled by Schneider PLC, which can realize the precise filling, stable performance and easy parameter setting. Pneumatic part adopts AirTAC brand to ensure long-term stable operation. It is application for filling Acid, alkali materials, highly corrosive pesticides, 84 disinfectant, toilet cleaner, iodine, washing soap, etc.

Performance feature:

1. Nice machine appearance, reasonable structure, this is the most advanced new design thick sauce filling machine at present, machine can be customized with 4/6/8/12/14/etc filling heads according to customer's production capacity.
2. Adopts positive displacement plunger pump for filling, high precision, large range of adjusting dosage, can regulate filling amount of all the pump body as a whole, also can adjust a single pump slightly, quick and convenient.
3. Plunger pump filling system has features of no adsorbing drugs, good chemical stability, high temperature resistance, corrosion resistance, abrasion resistance, long service life, has unique advantages when fill some corrosive liquid.
4. Used for various viscosity liquid filling, frequency control, automatic count.
5. Main electrical elements adopts foreign well-known brand.
6. Machine body is made of 304 stainless steel, full compliance with GMP standard.

Technical Parameter

- Model: YB-JG6
- Filling head number: 6
- Filling volume: 50-1000ml
- Capacity: 10-40 bottles/min
- Filling accuracy: $\leq \pm 1\%$
- Pass rate: $\geq 98\%$
- Power supply: 1 Ph. AC220V, 50/60Hz
- Total power: 3.8 KW
- Net weight: 750kg
- Overall dimension: L2200 × W1500 × H1650mm