

Pillow Type Packaging Machine HTL-280B/350/450/550



Features:

- Double frequency converter control (servo motor can be selected), the bag length is set and cut immediately, there is no need to adjust the empty walk, one step in place, saving time and film.
- Man machine interface, convenient and fast parameter setting.
- Fault self diagnosis function, fault display at a glance.
- High sensitivity photoelectric eye color mark tracking and digital input of sealing and cutting position make the sealing and cutting position more accurate.
- Temperature independent PID control, suitable for all kinds of packaging materials.
- Positioning stop function, no sticking knife, no waste of coating.
- The transmission system is simple, the work is more reliable and the maintenance is more convenient.
- All controls are realized by software to facilitate function adjustment and technical upgrading.

Scope of application:

It is suitable for the packaging of all kinds of regular objects such as moon cake, Mitong, snow cake, egg yolk pie, chocolate, candy, bread, instant noodles, biscuits, drugs, daily necessities, industrial parts, cartons or trays.

Technical Parmeters:

Model	HTL-280B	HTL-280E	HTL-350
Film width	Max.280mm	Max.180mm	Max.350mm
Bag length	90-220 or 150-330mm	20-115 or 45-90mm	90-220 or 150-320mm
Bag width	50-140mm	30-80mm	50-170mm
Product height	Max.40mm	Max.35mm	Max.40mm
Rewind diameter	φ300mm	φ300mm	φ300mm
Packing speed	50-250(bag/min)	60-350(bag/min)	50-250(bag/min)
Voltage	220V/380V 50HZ	220V/380V 50HZ	220V/380V 50HZ
Power	2.5KW	2.5KW	3KW