



Granule Packing Machine **DXDB-K80C**



Characteristics:

1. The back sealing granule packing machine comes with PLC programmable control and an English and Chinese display screen, making it easy to operate and maintain. It is easy to adjust.
2. A photoelectric tracking system and two-way compensation function of the granule packing machine ensure correct and accurate double-face printing and counting.
3. The packer shell, made of full stainless steel, is highly corrosion proof and easy to clean.
4. The back sealing granule packing machine uses a measuring cup for dosing.
5. Options for cutting way: saw-tooth cutting, and dashed line cutting
6. Options: ribbon coding machine

Usage:

The back sealing granule packing machine is used for packing granule materials such as sugar, salt, seeds, coffee, and so on, into small bags. It is used in the pharmacy, food, and agriculture industries.

Main Technological Parameters:

Item / Model	DXDB-K80C
Pouch length	50-120mm (adjustable)
Pouch width	20-80mm (should change bag former)
Packing speed	30-50 times/min (based on material and bag size)
Filling capacity	1-50ml
Cutting	Flat cutting, with tear notch.
Applicable film	PET/AL/PE, PET/PE, NY/AL/PE, NY/PE, etc.
Electric source	380V 50Hz (as per customer's request)
Total power	1 Kw
G.W.	260 Kg
Package size	1100*800*1600mm(L×W×H)