

## Multi lane Liquid Stick Bag Packing Machine + Peristaltic Pump GH280BY / GH560BY



### Feature:

1. Famous brand PLC control, system, large touch screen, convenient to operate;
2. Advanced design, high precision and fast speed;
3. No film alarm, saving materials and no waste film;
4. Photocell tracking system for precise bag length and position of film



**Parameter:**

| <b>Model</b>       | <b>GH280BY</b>  | <b>GH560BY</b>            |
|--------------------|---|---------------------------|
| Lanes number       | 4-6 lane  | 4-10 lanes                |
| Capacity           | 35 bags/min/lane  | 35 bags/min/lane          |
|                    | basic on produce and film                                     | basic on produce and film |
| Measuring method   | 1~ 50ml   | 1~ 50ml                   |
| Measuring Accuracy | ±2%   | ±2%                       |
| Measure Model      | 1. Piston pump; 2.Gear pump; 3.Peristaltic pump; 4.Rotor pump |                           |
| Bag size           | L:50-180MM  | L:50-180MM                |
|                    | W:17-40MM   | W:17-85MM                 |
| Sealing type       | Back sealing/stick bag  | Back sealing/stick bag    |
| Film width         | Max.280mm   | Max.560mm                 |
| Film thickness     | Laminated film thickness:0.07--0.10mm                         |                           |
| Cutting type       | 1.Flat Cutting; 2.Zigzag cutting; 3.Continuous cutting;       |                           |
|                    | 4.Round cutting; 5.Customized special shape cutting           |                           |
| Control system     | PLC+Servo+Touch screen  | PLC+Servo+Touch screen    |
| Air consumption    | 0.8 MPA 0.6M3/MIN   | 0.8 MPA 0.6M3/MIN         |
| Power Supply       | 3.5KW, 1N+PE/50HZ/AC220V                                      | 5KW, 1N+PE/50HZ/AC220V    |
| Dimension          | L1385*W918*H2005mm  | L1685*W1300*H2005mm       |
| Weight             | 350KG   | 450KG                     |