

Granule Food Packing Machine AMSFM-TD500



Brief Introduction of Granule Food Packing Machine

The granule packing machine is a new chain transmission type packaging machine, adopts automatic PLC control system and advanced CPU to guarantee accurate packing and reliable performance. It can realize the whole process automatically from bags making, weighing, and counting to sealing which has greatly improved the working conditions. Our granule food packaging machine is ideal equipment for automatically packing granule materials like foodstuff, medicine, seeds, chemicals, etc.

Characteristics:

1. Made of stainless steel, comply with GMP requirements, corrosion proof, clean and reliable.

2. Adopts PLC controlling device, advanced CPU and best power supply so that all the parameters can be installed and adjusted easily.

3. Accurate photoelectric trace system: with the speed of 20-70 bags/min, the error is less than 0.5 mm.

4. The length of bag is set by computer which can avoid the trouble at changing the gears and adjust the length by hand.

5. The special alarm functions for specified output and also can display the packing speed.

6. High automation degree, it can finish bag making, blanking, measure, count, sealing and photoelectric trace in one process.

7. The printer can print 1-3 lines of number, best before date, production date and so on, or you can select according to your requirements.

8. Multifunctional packaging machine, also suitable for packing crips and other irregular shape materials.

Application:

* This granule food packing machine is suitable for packing various granule materials like rice, peanuts, seeds, sugar, salt, tea, instant food, puffed food, medicinal granules, Chinese herbal medicine, etc.

* Suitable for automatic packing in food processing factories, medicinal industry as well as chemical industry.

Warm Tips of Granule Food Packing Machine

Packing Materials:

☆ Hot sealing composites, such as Cellophane/PE, BOPP/PE, PTP/PE, etc.

 \Rightarrow Please regularly check the parts of the machine once a month, find the defects need to be repaired in time and insure normal operation.

 \bigstar If no use of the packing machine for a long time, you should spray with rust preventive oil on the glossy parts, and cover with a tarpaulin on the machine.

Technical Parameter:

Model	Bag size	Capacity	Filling range	Power	Heater	Dimension
AMSFM- TD500	L:50-200mm W:50- 140mm	20-70 bag/min	100- 500ml	220V/550W	110V/250W	1100*900*1900mm