Vertical High Speed Sticker Labelling Machine SBSL-150-B

The Om Bhagwati Labelling Technologies's Automatic Vertical High Speed Sticker Labelling Machine Model SBSL-150-B, is one of the most user friendly. The Machine incorporates latest sophisticated Micro Processor Control Label Dispensing system with user friendly Sensing system for Label and Product. The Machine is suitable for Labelling on Round Bottle, Jars and other round objects. It is capable of Labelling up to 150 Products per minute depending on products diameter and label size.

Machine is suited for Glass, Plastic, Aluminum, PET bottles / jars of Pharmaceuticals, Mineral Water, Food Products and Pesticides having bigger Label Height and Length.

The Om Bhagwati Labelling Technologies's Sticker Labelling Machine SBSL-150-B has its own unique single point synchronized speed control system. The Inbuilt Automated Label Length detection systems eliminates any need for manually feeding and storing of Label Length data in memory and retrieving the same every time for change of Label Size & re-starting the machine. The System thus saves valuable time, avoiding machine-down time, and helps achieve higher production.

Machine can be supplied with Optional Toughened (Tampered) Glass or Acrylic Safety Cabinet. Machines having required all basic features as a standard fitment to match the current market needs and also saves cost and time.

Features:

- No Label Data Input/retrievals require for any Label Size
- No Change Parts for Product and Label size
- Synchronized speed of Label Dispensing, Conveyor and Pressing Device
- Virtually Maintenance free machine

- Easy to change label application height
- User Friendly Label Placing Adjustments
- Suitable for On-Line InkJet and Contact Coding System
- Suitable for Partial, Full Wrap Around and Overlap Labelling
- Built In A.C. Variable Frequency Drive System.
- Fully Stainless Steel finish Machine.

Technical Specifications:

Model No.	SBSL-150-B
Label Height	8 mm to 90/120/150 / 250 mm Standard*
Label Length	12 mm Minimum
Label Roll Dia.	400 mm
Core Dia.	75/76 mm
Gap Between two Labels	appx. 3 mm
Product Diameter	15 mm to 90 mm*
Electrical	220 VAC Single Phase Power Supply (50/60 Hz)
Power	1.5 Amp.
Capacity	0.75 Kw
Speed	Up to 150 Labels per minute depending on Product and Label Size
Conveyor height	830-950 mm* (Adjustable)
Overall dimension	1900 mm(L) X 1050 mm(W) X 1425 mm (H)
Machine Directio n of Movement	Left to Right from operator side