

Semi-Auto L Sealer & Shrink Tunnel FQL450A + BS-A450



The tunnel shrink machine FQL-450 + BS-A450 is a semi-automatic high-performance pneumatic line, which is used for fast group packing of goods in shrink film. The operation of the machine is carried out with the involvement of the operator, who preliminarily wraps the cargo in film, delivers the finished packaging to the shrink tunnel and after passing through the tunnel takes the finished packaging.

Specification: FQL450A Semi-auto L Sealer

Model	FQA450
Power Supply	AC220-240V/50-60Hz
Power	1000W
Seal-cut time	0-3sec
Conveyor time	0-10sec
Conveyor loading	25Kg (max)
Conveyor speed	0-10m/min
Film thickness	0.015-0.08mm
Max.sealing dimension	L500mm×W450mm(L+H≤500, W+H≤450mm)
Machine size	L1720mm×W730mm×H1050mm
Suitable for film material	POF, PVC

Specification:BS-A450 Shrink Tunnel

Model	BS-A450
Voltage	380V/3PH 50-60Hz
Power	10.3kw
Conveyor speed	0-10m/min
Tunnel size	1000*450*250mm
Heater type	Stainless steel heater
Heater size	370mm*15
Conveyor loading	10kg
Machine size	1260*670*1300
Suitable for film material	POF, PVC