

GOLDEN LIN

Automatically Shrinking Sleeving Machine LS series



Features:

1. The stainless steel constructed machine body ensures superior rigidity and stability. Additionally, it features a light weight design for better mobility and a more pleasing appearance
2. Equipped with CE level compact gear reducer, ensuring quality standard and performance
3. This machine is manufactured and operated to completely comply with CE standard for utmost quality and safety
4. Employing drive and control systems from Mitsubishi for best compatibility and convenient maintenance
5. Advanced human-machine interface from a world-famous brand, combining indicating light built-in buttons, featuring user-friendly operation
6. Designed with the new concept of simultaneous labeling system, the machine is excellent to be applied and furthermore integrated with plastic bottle production lines. The label positioning procedure is completed simultaneous with the conveying speed. With its advanced control and software, it is easy to make adjustment and additionally, equipped with high performance DC motor for added value
7. All the optical fiber sensors adopted on the machine are from high quality, world-famous producers to ensure the best accuracy
8. The machine's multi-function features make it possible to utilize the machine with diverse devices or equipment to fulfill various production need
9. The high quality machine is available at competitive price and it promises 100% customer satisfaction.

Specifications:

Model	GLS12250(E)	GLS-12300(E)	GLS-12350(E)
Machine dimension	L1150*W1300*H2050mm	L1150*W1300*H2050mm	L1150*W1300*H2050mm
Machine weight	550 kgs	550 kgs	580 kgs
Electronic Power	AC, 3 phase, 220V(380/415/440V)		
Speed	270BPM	320BPM	380BPM
Bottle diameter	35-125mm	35-125mm	35-125mm
Bottle height	Max. 320mm	Max. 320mm	Max. 320mm
Bottle material	Glass, Metal, Platic	Glass, Metal, Platic	Glass, Metal, Platic
Bottle Shape	Round, Oval, Square, Rectangular		
Film material	PVC, PET, OPS, PLA	PVC, PET, OPS, PLA	PVC, PET, OPS, PLA
Film thickness	0.035--0.08mm	0.035--0.08mm	0.035--0.08mm
Film Height	Max. 250mm	Max. 250mm	Max. 250mm
Inner diameter of sleeve roll	5"-10"	5"-10"	5"-10"