



## *XHL-AV6T-6G High Precision Liquid Filling Sealing Machine*



AV6T-6G is improved and developed from the same product overseas, combining new design and advanced technology, and multiply parts of function. Make the product more convenient in operate, adjustable, clean and maintain. The volumetric pump is high filling precision and stability. It is widely applied to daily chemical and oil product, filling more kinds of light and heavy liquid. Adopt the pneumatic cylinder driving, easy to adjust the filling volume, compact and good appearance.

### **Features**

- With 6 filling heads and 6 cylinders, quick and accurate filling precision.
- With Germany FESTO and Taiwan's AirTAC pneumatic components and Taiwan's electrical control parts adopted, its performance is stable.
- Quality guaranteed by employing Korean AUTONICS photoelectric sensors, Taiwan's PLC: touch screen and frequency inverter, and Schneider Electric Co.' electrical components.
- Compact design, attractive appearance, convenient installation and filling adjustment, no missed filling and accurate filling dosage with a counting meter provided. Filling nozzle head closure plug, preventing drip leakage, filling elevating system preventing bubble foaming. Bottle top positioning system and liquid level control system provided.

**Technical Parameter:**

Filling speed:	20-50 BPM
Power supply:	220/110V 50/60Hz
Power output:	0.5kw
Filling accuracy:	$\leq\pm 1\%$
Air pressure:	0.5~0.7MPa
Filling volumes range:	25~60ml 50~125ml
	100~250ml
	200~500ml
	400~1000ml
	900~2500ml
	2200~5000ml