

## *VD-2\_OT Automatic Filling Machine*



This automatic filler is designed to fill liquid, semi liquid, viscous (paste) and products with particles into the glass and jars & bottles.

### **TECHNICAL SPECIFICATIONS**

- \* Works with volumetric piston system.
- \* Works with oil-free pneumatic system.
- \* Touch Panel Control System
- \* Easy to adjust the filling range from by numerator and the hand wheels.
- \* The parts on the machine are connected by tri-clamps. They can be easily dismantled. The nozzle, main valve and the filling piston are designed for an easy-cleaning .They can be dismantled easily without using any tool.
- \* Optionally CIP system for sterilization of the filler.
- \* This machine has a various types of filling nozzles according to the product to be filled with an anti dropping system.

### **MATERIALS USED ON THE FILLER**

- \* The parts that contact with the product are 316 L stainless steel. The other parts are aluminum and 304 L stainless steel.

OPERATING TEMPERATURE: +5 ° - +90 °

FILLING ACCURACY: ± %1

Model	Minimum Filling Range (ml)	Maximum Filling Range (ml)	Filling Pistons	Capacity (Packages / Hour)
VD 1000-2_OT	100 ml	1000 ml	2	1200 Packages / Hour
VD 2000-2_OT	200 ml	2000 ml	2	1000 Packages / Hour
VD 5000-2_OT	1000 ml	5000 ml	2	840 Packages / Hour

