

Automatic Pouch Packing Machine for Food HT-8G/H












Description:

It suits for packing all kinds of grains and solids: Frozen dumpling, meat, dates, candy, nuts, pet food, tobacco, raisins, seeds, cereal, fruit, potato chips, chocolate, bread, biscuits, cakes, expanded food and bulk food etc.

Application:



Pouch Drawing & Samples:

								
stand up pouch Doypack	stand up pouch Doypack + e-hole / optional shape	stand up pouch Doypack + cut	stand up pouch Doypack + zipper + cut	flat pouch	flat pouch + e-hole / optional shape	sachet + zipper	sachet + e-hole / optional shape	sachet + overlap bottom



Machine Function:

Main Electrical Components:

- * SIEMENS PLC
- * SIEMENS HMI
- * OMRON
- * SCHNEIDER

Main Pneumatic Components:

- * SMC Solenoids & Cylinders

Guarding:

- * Glass Door Alarm
- * Air Pressure Abnormal
- * Automatic detection

Functions:

- * Tool-less changeover (pre-close zipper)
- * Horizontal in feed belt
- * PLC adjust bag width clamping
- * Included Vacuum Pump
- * Internal grooved cam design
- * Newest zipper open device
- * Two sealing stations
- * Nitrogen gas flush
- * Pouch shaker
- * Pouch out feed conveyor
- * Stainless Steel shell: SS304
- * Date coding
- * Air: 0.6m³/min

Main Technical Parameter:

Model	HT-8G/H
Packing Range (bag size)	Width 80-200mm, Length 80-350mm
Packing Weight	5-1500g
Capacity	30-60 bag/min (speed depends on filling product & weight)
Packing Precision	Error<±1%
Pouch Type	Stand-up bag, Flat bag, paper bag, laminated material etc.
Total Power	5 kw
Compressed Air Consumption	0.6 m ³ /min
Voltage	3 Phase 380V 50Hz/60Hz
Machine Dimensions	(L)4255*(W)1800*(H)3700mm
Machine Weight	2370 kg
Note:	1. According to the customer request, provides the special design. 2. The machine disposition may make the choice.