



## *Link-50CG Semi Automatic Carton Box Sealer Machine*



Link-50CG medium-speed folding cover and sealing machine is driven by belts on both sides, adopts sticky tape to seal, automatically folds the top and bottom to seal the box, fast and stable, and the sealing effect is smooth, standardized and beautiful, and can be adjusted manually according to the carton specifications Width and height, simple, fast, convenient, can replace labor, improve production efficiency by up to 80%, save 5-10% of consumables, is a good choice for enterprises to save costs, improve production efficiency, and achieve packaging standardization. This carton sealing machine is also known as medium-speed folding and sealing machine. It is suitable for high-speed folding and sealing. It can be adjusted manually according to the size of the carton. If you need to automatically adjust the size of the carton, it is recommended to use automatic folding and sealing machine (automatic adjustment).

### **Features of carton sealing machine:**

- .Manufactured with international advanced technology, and selected imported parts and electrical components;
- .It can be used with automatic balers of different brands;
- .Standard machine table height is 600/650mm;
- .When changing the size of the carton, manually adjust the width and height;
- .Automatically fold the cover at high speed, and seal the top box at one time;
- .Equipped with blade guard. Avoid accidental stabbing during operation;
- .It can be combined with Link-50G corner sealing machine to complete I-shaped sealing.
- .It can be operated on a stand-alone machine, or it can be used in conjunction with an automated packaging line. It is the choice for enterprises to save costs, improve production efficiency, and achieve packaging standardization.

## Application range of sealing machine:

Relying on the above advantages, the automatic folding cover and sealing machine is widely used in food, medicine, beverage, tobacco, daily chemical, hardware, toys, electronics and other industries at home and abroad.

## Technical Parameters:

Model	Link-50CG
Applicable to the power supply	220V/50Hz / 0.4KW
Work pressure	5-6 kg /cm <sup>2</sup>
Minimum packing size	L 200 * W 140 * H 130mm
Maximum packing size	L 600 * W 500 * H 500mm
Mesa height	H 600mm-650mm
The belt speed	28 m/min
Packing tape	BOPP/Kraft Paper Tape
Tape size	W48, 58, 72mm
Installation dimensions	L 1780 * W 930 * 1510mm
The net weight	200Kg