

High tightness paper wrap round noodle packing machine



Category: automatic wrapping machine

Product Name: High tightness noodle wrapping machine

Model: HZ --- 300 ~ 500 HZ --- 700 ~ 1000

Product Description:

Composition: Universal strapping; high tightness wrapping machine; sealing machine, can be customized according to customer demand.

Purpose: Noodle through accurate measurement after weighing machine into the strapping strapping, strapping face after falling into shaping device by lifting device (a head Qi), surface plastic wrapping machine after being sent to complete the package, and then by automatic sealing transported to the bench after sealing machine.

Work object:

Noodle Length: (180mm ~ 240mm) ± 5.0mm

Noodle thickness: 0.6 ~ 1.4mm Noodle width: 3.0mm or less

Packing speed: 15 to 20 packs / min Metering range: 200 to 500 500 to 1000

Measurement value is set: Digital Input Method Measurement value display: accurate to 0.1g

Measurement speed and accuracy: The noodle bar vary depending on the quality and quantity of

packaging

Device dimensions: 4000mm × 900mm × 1500mm

Power: AC220V / 50-60Hz / 2.5kW

<u>Advantages:</u> high packing tight, simple, reasonable structure, attractive appearance, and so on.

Benefit analysis:

This product is a high degree of automation, and has an automatic flush surfaces, automatic sealing function, compared to the traditional manual package surface, its efficiency is improved by 4-6 times, packaging costs about one-third of the past, and greatly reduced labor intensity.