

HG Two Section Temperature Control Electric Shrink Tunnel (Motorized Height Up/Down) (SH-AK15)



INFORMATION

1. Exclusive design of "tunnel auto-rise/drop when detecting alarm signal" helps prevent bottle deformation due to overheat.
2. All SUS304 stainless steel frame, elegant and compact, non-coating process, pollution free.
3. 3-step heat isolation design for energy saving and operator protection.
4. Digital control, internal circulation keeps temperature consistent and shrinking effect perfect.
5. Equipped with high-level VFD (Variable Frequency Drive) that makes controlling of wind speed easy.
6. Unique wind board design makes controlling of wind direction easy and flexible, able to adapt to different bottles.
7. Durable electric (quartz) heater tube ensures efficient heating.
8. Panel is embedded to prevent operators changing setting accidentally.
9. Heating can be stopped immediately, or maintained by timer.

SPECIFICATION

機型 Model	SH-AK15
三層不鏽鋼隔熱爐體(0.75米) Tri-layer of Heat Insulation Framework (0.75 meter)	2 sets
恆溫電力調整器數位溫控器 Digital Thermo-Regulator	2 sets
模組化風輪組 Module of Circulating Fan	2 sets
可替換式模組化吹風板 Replaceable Module of blowing Pore Board	2 sets
石英電熱管 Electric Heat Tube	12 sets
風量變頻控制 VFD Control	2 sets
長×寬×高(mm) Dimension(L x W x H)	1500x450x1750mm
電源 Electric Power	AC 3ψ 5-9KW
重量 Weight	30kgs