

DPP-360SL High Speed Roller Blister Packaging Machine



Features

1. High-precision worm gear reducer with large torque and increased service life.
2. Equipped with air pressure and water pressure controllers. When the pressure value is lower than the set value, the display screen will display the fault and alarm and stop.
3. The main station bearings are all imported from Japan NSK brand.
4. Solenoid valves, vacuum valves, etc. are all imported from Japan SMC brand.
5. Multiple sets of silicone disc brushes are used to effectively improve the feeding rate. In view of the difficulty of feeding special-shaped pieces, this structure can increase the filling rate of medicines by 20-30%.
6. The steel character printing method is hot extrusion, and heating the steel character plate makes the printing clearer and more efficient.

Specifications

Punch Speed:	20~40 times/min
Production Capacity:	250,000~500,000 capsules/hour
Optional range of feed stroke:	40-120 mm
Max Forming Area:	245~350×112mm
Maximum Forming Depth:	Alu/Alu12mm
Upper and lower forming heating power:	2KW (×2)
Heat Seal Heating Power:	1.5~2KW
Overall Dimensions:	4800×900×1740mm
Machine Packaging Size:	5500×970×1840mm
Weight:	3000~4000Kg
Motor Power:	1.5~2.5KW
Air Pump Volume Flow:	≥0.25m ³ /min
Heat-seal aluminum foil:	0.02×250mm
Medical PVC:	0.25 (0.15-0.5) ×250mm
Heat-seal aluminum foil:	0.02×250mm
Total Power:	3-phase 4 wire 380V 50HZ (220V 60HZ) 7.5~8.5KW