

Rotary tablet press ZP5C, ZP7C, ZP9C



This machine is a single press type, continuous automatic tablet press for pressing granular materials into various tablets, such as round or irregular tablets.

This machine is widely in lab, hospital, or pharmacy, foodstuff, chemical and electric industries.

Features:

- 1. The outside part of this machine is full-enclosed, the material of the cover and the inside table face is stainless steel. The turret face is specially disposed keeping the luster of the face and prevent the cross pollution, meet the GMP standard.
- 2. The machine has transparent windows so that press condition can be observed clearly and the window can be opened cleaning.
- 3. The lay-out of all the controllers and operation parts is reasonable.
- 4. The speed is adjusted by frequency conversion.
- 5. With overload protection equip is included in the system to avoid the damage of the punches and apparatus, when overload occurs the machine stops automatically.
- 6. The volume is small, the weight is light, and the gross weight is only 220 kg, so that the machine can be express delivery or air cargo easily.

Technical data:

Model	ZP5C	ZP7C	ZP9C
Max.pressure(kn)	40	40	40
Max.diameter of tablet(mm)	12(irregular 14)		
Max.depth of filling(mm)	15	15	15
Max.thickness of tablet (mm)	6	6	6
Turret speed(r/min)	0-36	0-36	0-36
Max.capacity(pc/h)	10000	15000	19000
Power(KW)	1.5	1.5	1.5
Power supply	customization		
Gross weight (kg)	220	220	220
Packing size(mm)	650*600*1150		