



## *Semi Automatic Cartoning Machine SBPL SAC 60*



To increase the production and efficiency, we have specially designed Semi Automatic Cartoning Machines. Our Semi-automatic cartoning machine speeds up the cartoning process in every possible way. The horizontal semi-automatic cartoning machine manufactured by us is ideal for pharmaceuticals. It is also suitable for a wide range of bottles, containers pouches, blister packs, etc. Thus we are famous exporters of it from India..

This Cartoning machine is suited to handle such items as tubes, blister strips, bottles, vials, ampoules, droppers, inhalers, film rolls, bearings, soaps and many other products falling within the wide range of the machine either individually or in combination.

Automatic Cartoning Machine draws the carton from a magazine & opens the carton, Inserts product and closes the carton by tucking in the flaps.

This Cartoning machine is suited to handle such items as tubes, blister strips, bottles, vials, ampoules, droppers, inhalers, film rolls, bearings, soaps and many other products falling within the wide range of the machine either individually or in combination.

Applications this machine can successfully be used for Cartoning Tubes, Cosmetics, Soaps, Bottles, Ampoules, Vials, Bearings, Blisters or any other rigid products that goes into a unit carton. Multi packs of more than one product in a unit carton can also be handled in this Cartoning Machine.

Leaflet insertion: An automatic insertion of pre-folded leaflets is also possible with an leaflet pre-insertion device.

**Technical Specification:**

| <b>Model</b>                                       | <b>SBPL SAC 60</b>           |
|--|------------------------------|
| <b>Box Size</b>                                    | Max. 80 x 80 x 200mm (L*W*H) |
|  | Min. 15 x 8 x 40mm (L*W*H)   |
| <b>Leaflet Size (Incase of) -4 Manually folded</b> | Max. 200 x 60mm (L*W*H)      |
|  | Min. 100 x 8mm (L*W*H)       |
| <b>Output Speed</b>                                | 20 to 60 boxes/min. max      |
| <b>Working Height</b>                              | 700 +/- 50mm                 |
| <b>Power Consumption</b>                           | 0.5 HP, 0.37 KW              |
| <b>Power supply</b>                                | 1 Phase, 230 V, 50 Hz        |
| <b>Air Supply</b>                                  | 9Kg/cm <sup>2</sup>          |
| <b>Air Consumption</b>                             | 10 CFM                       |
| <b>Net Weight</b>                                  | 350 Kg.                      |
| <b>Dimension</b>                                   | 750 x 850 x 1200mm (L*W*H)   |
| <b>Carton Paper Thickness</b>                      | 250 gsm / 300 gsm            |
| <b>Leaflet Paper Thickness</b>                     | 500 gsm / 60 gsm             |