



LC-1800 Shrink Tunnel



Application:

For shrink-packaging various products, such as general foods, electronic products, stationery, gift boxes, daily appliances, medicine, salted products, hardware, tools, electrical appliances, bamboo and wood products.

Features:

- Employs infrared ray titanium heater tube for greater heating capacity while saving power
- Efficient hot air circulation in the oven combined with uniform temperature distribution provide fast shrinking performance
- Feed conveyor is driven by a variable speed motor for convenient speed adjustment
- Full shrink is quickly accomplishment in only three seconds
- Feed speed may be adjusted to over 7.5 meters per minute
- Fast warm-up permits for operation-ready status in only 10 minutes

Model	LC-1800	LC-2000	LC-3000
Power Source	380V	380V	380V
Heating	27kw	40kw	54kw
Shrink Tunnel Dimensions	1800 x 700 x 00 mm	2000 x 900 x 500 mm	3000 x 1000 x 500 mm
Machine	2600 x 1000 x 1650 mm	3200 x 1200 x 1750 mm	4500 x 1300 x 1750 mm
Packaging Size	600 x 300mm	800 x 400 mm	900 x 400 mm
Motor	1/2 HP x	1/2 HP x 3	1/2 HP x 4, 1HP x 1
Conveyor Speed	0 – 8 m/min	0 – 8 m/min	0 – 8 m/min