

TY-37J POF Shrink Tunnel (High Speed)



From table type to high production type, the wide range of TAYI YEH shrink packaging machines are quality designed and engineered to give extraordinary performance.

Features

- Machine constructions use S-41 steel material.
- Machine frames formed up by model.
- Specified spare parts kit.
- Live roller rod conveyor.
- Speed changeable motor with speed desired & adjusted easily.
- Fully re-circulating heating air.
- Highly efficient heating up with good separations.
- Temperature controlled automatically.
- Temperature variable with easily operation.
- SUS thermocouple systems.
- SUS 304 stainless steel inner tunnel.
- SUS 304 stainless material wires & terminals, covered with ceramic guards.
- CE model availale.

Specification

MODEL	CHAMBER MM	OVERALL (L x W x H) MM	PACKAGE (W x H) MM	CONVEYOR SPEED (MPM)	POWER	CONSUMPTION KW
TY-37J POF	1600x500x300	2000x960x1140	380x220	0-25	220V / 380V	18
TY-50J POF	1500x500x300	2090x820x1590	300x150	0-25	220V / 380V	18

^{*} Specifications Subject to change without prior notice.

Applications

Suitable for food, gifts, hardware, daily-use products, electronics, electrical industries, medicines, bamboo ware...etc

^{*} Production capacity is subject to product size, type of product, shrink film material and shrink film thickness. ** Specifications are subject to change without prior notice.