



## ***MBB480K / MBB720K / MB960K Automatic Multi Line Four-Side Sealing Cup System Packing Machine***



The machine is widely used in the fields of food, daily chemical, medicine, etc, to package granules and powder. The main performance and structure characteristics, control components of PLC, touch screen and easy and convenient operating system

### **Description:**

The fully automatic linear digital weigh metric machine with liner or electronic digital weigher system is most economical solution for packaging need of many industries. Our machine form bags, sachets or pouches using lay flat flexible rolls, and fill the material and finally seals them, this machine is used to make four side sealed pouches/ sachets/ bags. Advanced design, high precision, fast speed, high efficiency, No film automatic stop function, saving material, avoid waste. Heat sealing bag system with photoelectric bag length track; ensure that bag fast smooth and accurate

### **Packing Materials:**

It's suitable for any heat sealable compound material such as single Paper/PE, Cellophane/PE, Aluminum foil /PE, BOPP/PE and Nylon/PE. Custom specifications are available to meet specific requirements.

### **Features:**

- Auto Weigh Filling System Fully Automatic For filling light and Fragile Products High Quality Very easy to operate User friendly program with 2-line LCD Display
- Main contact parts are made of stainless steel
- Compact design with caster wheel for easy mobility
- Online Vacuum/ Nitrogen Flushing System
- Online Pneumatic Batch Coding
- Most of the operation by Pneumatic control
- Photocell control system can automatically adjust & correct "Eye Mark" with +-2mm
- Unique weigh metric digital weighing system
- PID temperature control

#### Optional Device:

- Date Pinter
- Nitrogen Flushing Arrangement
- Belt Conveyor
- Bucket Elevator
- Level Sensor Devices
- Ultra Violet System
- Servo Stabilizer

#### Specifications:

Model Type	MBB480K	MBB720K	MB960K
Motor (V/HZ)	AC 220V/50Hz 110V/60Hz	AC 220V/50Hz 110V/60Hz	AC 220V/50Hz 110V/60Hz
Power (W)	2800	3500	4500
Cavity (line)	4-6line	4-10line	4-12line
Capacity (bags/min)	35-75	30-60	30-50
Packing Capacity (g)	4-200	40-400	100-1000
Length of Bag (mm)	45-120	45-120	45-120
Width of Bag (mm)	35-60	35-90	35-120
Max film Width (mm)	480mm	720mm	960mm
External Dimensions (mm)	L950*W1470*H2030	L1153*W1654*H2030	L1415*W1686*H2030
Net Weight (kg)	750	950	1150