



JC-500 Fully Automatic High Speed Reciprocating Packaging Machine



High speed Shrink wrapping machine suit for grouped food and drinks, bowl noodles, milk tea, mosquito coils, wallpaper, exercise books, filters, electrical switches, a variety of stationery, industry parts, commodities and cosmetics, etc. Please click "[here](#)" to check all kinds of samples.

Description:

1. Driven by three servo motors, is easy to operate, high stability and high packaging efficiency. Fewer mechanical parts, greatly reducing the failure rate of mechanical parts, easy maintenance, less noise.
2. Reciprocating transverse seal cutter base design, beautiful appearance, and good sealing performance.
3. High sensitivity photoelectric eye color mark tracking, mathematically input the sealing position, so that the sealing position is more accurate.
4. The side seal can be replaced by electrostatic adsorption, which can save the cost of packaging film and make the sealing line smoother and more beautiful.
5. Cantilever frame design fuselage, rugged and durable.
6. Temperature independent PID control, better to cut and seal the film
7. Location stop function, no sticking knife, no waste of film.
8. The transmission system is simple, reliable and easy to maintain.
9. When cut to the product, automatic inversion, restart directly after boot, more convenient operation.

Adding waste recycling device makes packaging more beautiful and saves about 20-30% material than traditional folding fill, packaging machine

Technical Parameters:

Machine model	JC-500	
Packing size	L	80mm-450mm
	W	20mm-200mm
	H	5-90mm
Packing speed	30-175pcs/min	
Max film size	≤590mm	
Film Type	POF PVC Shrink film	
Power consumption	3.6KW+16.5KW	
Power supply	Front part:220V,50HZ/60HZ: shrink tunnel:380V,50HZ/60HZ	
Front machine dimension	4900*1130*1500mm	
Shrink tunnel dimension	2600*600*1750mm	
Weight	1200KG+600KG	