

Granule Packing Machine XY-80BK



Main performance & characteristics

1. The whole structure: This machine integrates mechanical and electrical together. And the whole machine is controlled by PLC (Programmable Logic Controller).
2. Photoelectric on membrane: It adopts PLC control photoelectric correction system, and equipped with high-precision stepping motor, to ensure the integrity of the packaging film pattern, it can control the system of complete synchronization, length fixing, orientation and speed of whole machine.
3. Adjusted the bag length: If turn off on the membrane system, you can adjust the parameter to adjust the bag length, although the film width is fixed, so as to adjust the amount of packaging.
4. Measurement and sub package method: The machine according to the measuring cup size and measuring the regulating handle manually adjust to realize partial shipments and measurement function.
5. All functions: this machine is fully automatic machine. Can automatic accounting bag (film), on film, the date of printing (need to match the ribbon code printer linkage device), measuring, filling, sealing, cutting film, and so on.

This machine is applicable for packaging the foodstuff, pharmaceuticals, chemicals, agricultural chemicals, as well as the granules with little viscosity. It is applicable for packaging the puffing food, fried foodstuff, peanut, melon seeds, electuary, desiccating agents, aginomoto, white sugar, plant seeds, delergent, etc.

Technical Parameters:

Item	XY-80BK
Bag Size	W:80-200mm
	L: 80-280 mm
Capacity	25-50 bags/min
Measuring Scope	50-600g
Power	220V/50HZ/ 1.9KW
Weight	400kg
Dimension(L*W*H)	1000*900*2200mm
Controller	PLC
Warranty	1 Year
Contact product part	304 Stainless steel