

IN-LINE

Labeling Equipment, Inc.

7282 Spa Road North Charleston, SC 29418
Phone: (843)569-2530 Toll Free: (800)465-4630 Fax: (843)569-2531



Paradigm 700 Top-Down/Bottom-Up Labeler

The Paradigm 700 is a fully automatic label applicator capable of applying labels to a variety of products. Label application can be from the top down, bottom-up, or both. The machine is loaded with nice features; all stainless steel and aluminum construction, off-the-shelf components rather than proprietary boards and motors, a stepper-driven applicator and a standard touchscreen interface on all models. All speeds on every 700 are synchronized together to avoid common labeling errors, and our Autoset bottle measurement and recipe system ensure easy setups and changeovers. The Paradigm is capable of accuracy to $\pm 1/32$ " depending on the product. Products to be labeled are sensed as they pass a photo-eye. The photo-eye initiates a signal that is transmitted to the PLC. After a fully adjustable delay, the label is dispensed onto the passing product. For flat panels a wipe brush completes label application by wiping down the label onto the product. You can count on In-Line to offer the custom solution for your labeling needs. All In-Line machines are backed with a one-year warranty, and we are available to answer questions and troubleshoot. We don't leave you cold after the purchase. We develop a relationship with our customers and are here to help them as their business grows and changes. So, you can be confident when you partner with In-Line that you are receiving not only quality products, but quality service as well.



Labeling Equipment, Inc.

Features

- Label 1" to 5" non-round containers.
- Apply labels from 1" to 4 ½" tall and 12" long.
- Label can be moved up to 6" from base of container. 4 axes of adjustments.
- Accepts random or continuous bottle feed.
- Changeovers require no tools and take less than 10 minutes.
- Touchscreen Interface.
- Speeds to 100 bpm depending on label length.
- All variable speed conveyor, wrap station, top belt, and label speeds.
- High-speed counting on all delays.
- Maximum label roll size of 12".

Options

- Hot Stamp coding for lot/date information.
- Wrap Belt for round containers
- Extra Tall Label Kit for labels up to 7 ½" tall.
- Infeed Spacing Wheel powered by a separate DC motor.
- "Gallon" upgrade for containers up to 6½".
- Locking Casters

Specifications

Conveyor width:	4 ½"
Conveyor height:	33" Standard (+4" up)
Conveyor length:	84"
Conveyor motor:	1/4 hp DC geared motor
Overall machine width:	60"
Overall machine height:	72"
Overall machine length:	88"
Overall machine weight:	550 pounds
Labeling Head motors:	Stepper-driven
Power requirements:	120 volt AC, 60 cycle, 10 amp power
Compressed air:	3-4 cfm @ 65 psi



7282 Spa Road
North Charleston, SC 29418
Phone: (843)569-2530
Toll Free: (800)465-4630
Fax: (843)569-2531