

Automatic Pallet Wrapping Machines T-1650



The pallet wrapping machine is suitable for container transportation of bulk cargo and packaging of loose pallets. It can improve logistics efficiency, reduce loss during transportation, and has the advantages of dustproof, moisture-proof, and reduced packaging costs. It is an ideal choice for improving product packaging. Widely used in glass products, hardware tools, electronic appliances, papermaking, ceramics, chemicals, food, beverages, building materials and other industries.

Discription:

Pallet Wrapping Machine adopts programmable control (frequency converter), reliable in performance, convenient.

In operation; The lapping type and time can be designed on customers' requirements.

Equipped with a photoelectric detector, automatically testing the goods height and controlling the travel limit.

Rotary table can reset automatically, thus ensuring correction-and out position of the tray. Convenient in film roll Replacement, LLDPE film with outside diameter<280mm, width<500mm and paper core 76mm can be used.

Custom-mode specification is available and also providing a complete set of packing system of conveying line.

Model	T-1650
Turntable diameter (mm)	Φ1650
Wrapping height (mm)	2400
Column height (mm)	2700
Turntable height (mm)	78
Turntable load (kg)	1500
Electric source	AC220V, 50HZ
Power (KW)	1.5
Turntable speed (rpm)	0~12
Packing material	LLDPE Film
Film thickness (μm)	17~35
Film width (mm)	500
Film roll inner diameter (mm)	Φ76.2
Film roll outer diameter (mm)	240 (max)