

Three-dimensional transparent carton packaging machine BT-250&BT-400C



This product uses the multi-function digital frequency steeples speed regulation, PLC programming control technology, automatic feeding, automatic counting, and human-machine interface touch displays. Be equipped with micro-pump pneumatic falling film. Suitable for pharmaceutical, food, cosmetic, cosmetics, audio-visual products, rubber, IT and other industries exterior decorating the square boxed goods packaging. The machine can be linked production and cartoning machines, inkjet printer and other machinery.

The main technical parameters:

The machine's job is to rely on a series of cams inside the machine and the working parts of each link to be completed. Use of multi-function digital frequency variable speed, PLC programming control technology, automatic feeding, automatic counting, touch-sensitive display human-machine interface. Be equipped with micro-pump pneumatic falling film. Reasonable structure, advanced technology. The machine is suitable for larger items or a single box set of stacking boxes (bars) body-wrapping.

Specification	BT-250	BT-400C
Production efficiency	20-60 bags / min	10-20 bags / min
Package size range	(40-200)×(30-120)×(10- 50) mm	(100-300)×(50-200)×(20- 80)mm
Power supply	220 V 50Hz	
Motor Power	0.75Kw	
Electric heating	4kw	
Dimensions	3200×850×1600mm	2250×1100×2000mm
Weight	1000kg	1000kg
Scope	Single box or boxes (cartridge)	