



## ***Automatic Sleeve Sealing & Shrinking Packagers ST-6030A+SM-6040***



### **Features:**

- ST-6030A + SM-6040 automatic sleeve packager is the special design for single product or the things with tray, it can combine with production line, operate the feeding of the product, wrapping the film, sealing the film, shrinking the product, cooling the product together automatically
- ST-6030A adopts advanced technology and art design; ensure it works stably and reliably
- Film feeding is controlled by sensors to reduce the waste of the film
- Omron temperature controller ensures the accuracy of the sealing hot
- Speed of the feeding conveyor is controlled by a frequency inverter
- All operation controlled by PLC, integrate with the machine, electricity and gas work smoothly
- Adopted special design of sealing cutter to make sure sealing line deep-set, avoid film sticking the cutter
- Conveying belt can set on right or left depends on design and demand
- SM-6040 adopts double motors to blow the hot air reach every corner inside the tunnel to make sure the perfect performance of shrinking
- Adjustable heavy cool air ensure the shape of the shrinking perfectly

### **Scope:**

- This series of models using hot air circulation shrink, mainly shrink label for bottle-shaped bottle, jars, cups etc.
- For beverage, beer and mineral water, cans, glass bottles with tray or carton

## Specifications:

Model	ST-6030A	SM-6040
Machine dimension L×W×H(mm)	1382×2716×1991	2800×900×1690
Tunnel dimension L×W×H(mm)	/	1800×600×400
Max packing size L×W×H(mm)	500×300×300	1500×400×300
Sealing size L(mm)	700	/
Temperature ( °C )	0-200	0-400
Height of work table (mm)	850±50	850±50
Packing speed ( pcs/min )	8-18	25-30
Net weight (kg)	390	600
Power (kw)	1.5	24
Power supply	3PH 220V/380V 50/60Hz	3PH 220V/380V 50/60Hz
Air pressure ( kg/cm <sup>2</sup> )	6-8	/
Applicable film	PE	PE

