

JY-450/600 Automatic Reciprocating Flow Wrapping Machine



Main performance & characteristics

1. Double transducer control, flexible bag length cutting, operator needn't to adjust the unloading working, saving time and saving films.
2. Touchable human-machine operation, convenient and quick parameter setting.
3. Self diagnosis failure function, clear failure display.
4. High sensitivity optical electric color mark tracking and digital input cut position which makes the sealing and cutting more accurate.
5. Separate PID control to temperature, suitable for various packing materials.
6. Reciprocating type sealing device, firmer sealing, and no wasting in mold sealing cutter.
7. Terminal sealing device, more beautiful bag shape, improving products level.
8. Stopping the machine in selected position, no sticking to the knife and no waste packing film.
9. Simple driving system, reliable working, convenient maintenance.
10. All the controls are achieved by software, convenient for function adjusting and upgrading.

Usingrange

regular objects such as biscuits, pies, bread, instant noodles, drugs, daily appliances, industrial parts, paper boxes, plates, etc.

Technical parameter

Model	JY-450	JY-600
Packing speed (bag/minute)	20-80 bag/min	20-80 bag/min
Packing size (mm)	L120-450	L120-450
Length x Width x Height	W50-210	W50-280
	H10-120	H10-120
Maximum width of film (mm)	<450mm	<600mm
Thickness of film (mm)	>0.025mm	>0.025mm
Power	220V,50/60HZ,3.6KW	220V,50/60HZ,3.6KW
Overall size (mm)	4380*870*1500mm	4380*970*1500mm
Weight	950kg	1160kg
Package	3.1CBM.2CASES	3.6CBM.2CASES
Packing material	OPP/PP6, OPP/PP, PT/PE, PE, KOP/PP PT/PE/, AI_/PE etc. Any heat-sealable composite materials foil/film	