

HS350 Sugar Pillow Type Packaging Machine



The transducer also with the machine from Panasonic brand to keep machine work more stable.

Main performance and structural features

- * It's convenient in bag length control with advanced dual frequency conversion design;
- * Reasonable complete machine design and stable performance; simple in operation with PLC full computerization;
- * Precise sealing and cutting with high precision photoelectric tracking system;
- * Positioned stop function without sticking to the reamer and wasting the roll film

Technical Parameters

Item	HS-350	HS-350A	HS-350X	HS-350XA
Film width	60-350MM		MAX.350MM	
bag-making length	65-190MM/120-280MM	90-220MM/140-330MM	65-190MM/120-280MM	90-220MM/140-330MM
bag-making width	50-160MM		30-160MM	
production height	Max.40mm	Max.60mm	Max.40mm	Max.60mm
packing material	OPP/PE/PVC,OPP/CPP,KOP/CPP,ALU-FOIL		OPP/PE/PVC,OPP/CPP,KOP/CPP,ALU-FOIL	
thickness of film	0.03-0.07MM		0.03-0.07MM	
packaging speed	40-230bags/min		40-230bags/min	
power specification	3.4kw/220,50/60hz		3.4kw/220,50/60hz	
machine dimension	(L)4020*(W)770*(H)1450mm		(L)4020*(W)770*(H)1450mm	
gross weight	600G		600G	
optional device	printer, Air-filling device, feeder, Tidier, alcohol spray device		printer, Air-filling device,feeder, Tidier, alcohol spray device	