

## Automatic Servo Horizontal Packing Line HP-250D



## Features:

- 1. Controlled by double frequency converter, bag length setting by numerical input. No need of test running, save time and film.
- 2. Large touch screen, easy parameter setting and operation.
- 3. Fault self-checking function, fault display on touch screen clearly.
- 4. High-sensitive photocell tracking, and numeric input of cutting length, ensure more accurate sealing position.
- 5. Temperature controlled by PID independently, apply for various of film material.
- 6. Stop position can be set, non-stick sealing knife, no waste to film.
- 7. Opening design of main machine, product scraps drop down to keep the machine clean.
- 8. Machine controlled by computerized software, convenient for function adjustment and technical upgrading, never lag behind.

## Scope of application:

Apply to the packing of various kinds of items with regular shape in many industries, such as food, hardware, medical products, daily use products, stationary, toys, hotel supplies, electronic products etc.

## Specification:

opecinication.	
Model	HP-250D
Bag Length	60-190mm or 120-280mm
Bag Width	30-110mm
Packing Speed	40-230bag/min
Film Roll Diameter	Max. 320mm
Film Width	Max. 250mm
Product Height	Max. 55mm
Machine Weight	600kg
Machine Size	L3770×W670×H1450mm
Power Supply	220V/380V, 50/60Hz, 2.4KW