

## *CKDQL5545G/CKDSC4525L Automatic Box Heat Shrink Wrapping Machine*



This High Speed Box Shrink Wrapping Machine is widely used in foodstuff, drinks, printing, pharmaceutical, floor, hardware and other industries shrink packaging for packaging perfume box, cigarette box, detergent box, tea box, gift box, electrical box, milk box, book, notebook, phone box, etc. It is suitable for POF and PVC etc packaging material.

### **Features:**

1. The sealing knife adopts copper alloy sprayed with Teflon, it won't stick film, sealing fastness, without smoke, non-pollution. Horizontal and vertical sealing knife adopt whole connecting without gap, the film won't break. Sealing frame adopts high quality alloy steel, the sealing quality is stable, frame difficult to be damaged.
2. The machine has entire automatic system, it equipped with sensors can reach high speed automatic working.
3. It is convenient to adjust according to different sizes products, just adjust the handle wheel can reach it, operation is easy.
4. It can be connected with production
5. It has protection function to avoid sealing product wrong and ensure the safety of operator

### **Characteristic:**

1. It adopts Schneider AC contactor, high-power Solid state booster and intelligent temperature controller to make temperature system more accurate, prolong the working life.
2. It adopts solid roller conveyor, the rollers wrapped with high temperature silica gel tube. It can stand heavy product and difficult abraded (you can choose net type conveyor).
3. It adopts high-power fan motor to ensure enough strong wind to reach perfect packing effect.
4. Inside wall adopts stainless steel, it has fast temperature transfer, even heating, low energy consumption, long working life characteristics.
5. It is with visible window, can see what's going on inside.

## Technical Data

Model	CKDQL5545G	CKDSC4525L
Max packing size(mm)	L+2H≤550, W+2H≤450, H<130	W450×H250
Max sealing size(mm)	L550×W450	/
Power(KW)	1.30	9
Capacity	0-24m/min	0-16m/min
Voltage	220V 50/60HZ	380V 50/60HZ
Sealing temperature	180°C—250°C depends on thickness of film and environment temperature	
Thickness of film(mm)	0.015-0.10	
Air pressure(Kg/cm <sup>2</sup> )	5	
Packing material	POF PVC	
Machine weight(kg)	320	220
Machine size (mm)	L1700×W900×H1400	L1800×W703×H1260