

KD-260 Pillow Type Automatic Packing Machine



Compact structure, stable performance, simple operation. The third generation of three servo control, bag length is set and cut, no need to adjust the empty walk, film color tracking step in place, save time and film. Using imported electrical appliances, touch man-machine interface, parameter setting is convenient and fast. Fault self diagnosis function, fault at a glance. High sensitivity photoelectric eye color mark tracking makes the sealing and cutting position more accurate. Temperature independent PID control, better suitable for all kinds of coating materials. Positioning stop function, no sticking knife, no film. Simple rotation system, more reliable work, more convenient maintenance. All the control is realized by software, which is convenient for function adjustment and technology upgrade.

Technical Parameters

Equipment name	Pillow type packaging machine
Equipment model	Kd-260 automatic pillow packing machine
Use of packaging materials. And specifications	It is suitable for various OPP heat sealing film, composite film, coated paper, aluminum foil film, aluminum plastic composite film; 0.03-0.06mm
Model specification	4100*950*1500
Packaging speed	40-250 bags / min
Bag length	60-200mm
Package width	25-100mm
Packing height	5-45mm
Rated voltage v. power	AC220v.2.4KW
Compressed air pressure	0.5-0.7 (Mpa)
Compressed air consumption	> 0.36 (m ³ /h)
Noise (DB)	Low noise.60-70db
Machine weight kg	650Kg
Motor frequency modulation capability	0-50Hz
Automatic control capability of production process	Automatic code printing