

Model-657L Soup Packing Machine



Suitable for packaging liquid sauce products with granules and concentrations.

Edible: miso, jam, commercial sauce packets, white ash and other products.

Non-edible: refrigerants and other products.

Feature

- Fully gear of mechanical drive principal, with high stability and durability.
- All components in direct contact with product are made of stainless steel and P.P material, conforming to sanitary standards.
- With food grade lubricating oil for internal gears.
- The air compressor system is made by BOSCH Rexroth, three-point combination, electromagnetic valve imported from Germany.
- Incorporated three-way full-bore threaded-ends stainless steel ball valve-OMOL imported from Italy, the valve body is made of 316L (-20 to +160 degrees).
- All components in direct contact with product especially inner part of PISTON measurement filling are made from SS316L and food grade material. Equipped with easy opening device.
- Equipped with a product counting device.

Specification

Packing Type	Three Side Seal
Packing Weight	5-80g
Bag Length	L:50, 75, 80, 90, 100, 120, 150, 180, 200 mm (Designed according to customer order requirements, the machine cannot be adjusted after leaving the factory!!!)
Bag Width	W:30-80 mm
Packaging Speed	30-40 bags/ min (According to different products, filling weight, and film.)
Film Material	Various heat sealable materials (such as plastic film, aluminum foil + PE...etc.)
Machine Dimension	55(L) *100(W)*135(H)
Net Weight	200 kg
Electrical Requirements	1-Phase, AC 220V, 50-60Hz
Air Pressure	4 Bar