



DQL4518_DSC4525L Sealer Shrink Wrapping Machine



The L bar sealer shrink wrapping machine is suitable for mass shrink packaging in stationery, food, cosmetics, pharmacy, hardware and other industries. Imported PLC automatic program control is adopted, which is easy to operate and has safety protection and alarm functions, thus effectively preventing packages from being cut by mistake. Equipped with imported horizontal and vertical photoelectric detection, it is convenient to switch and select. It also has a close-fitting function and is specially designed for packaging small products. The whole machine can realize unmanned operation connection with the production line.

Features

1. Sealing strong and better performance of heat conduction-special durable alloyed sealing knife with anti-stick teflon coats
2. Easy to operate -only adjust packing width and height by hand wheels without changing any molds and parts when packing size changes. packing length can be detected by the sensor automatically.
3. Production line-Different products with different sizes can be packed together as promotional package.
4. Quality key parts -adopt Omron brand parts such as temperature controller, timer, relay, switch, and sensor.
5. Alarm for scrap film break or full.
6. A pair of photoelectric switch in vertical for thin products.
7. Optional closing conveyor for small products.
8. Optional sensor for transparent products.
9. Visible window in shrink tunnel.

Technical Parameters

Model	DQL4518	DSC4525L
Max packing size(mm)	L ∞, W+2H≤450, H≤150mm	Shrink tunnel: L1500*W450*H250
Max sealing size(mm)	W380	/
Power(KW)	1.40	9
Capacity	0-21 pcs/min	0-16 m/min
Voltage	220V 50/60HZ	380V 50/60HZ
Sealing temperature	180°C—250°C depends on thickness of film and environment temperature	
Thickness of film(mm)	0.015-0.10	
Air pressure(Kg/cm2))	5	
Packing material	POF PVC	
Machine weight(kg)	340	220
Machine size(mm)	L1700×W950×H1580	L1800×W703×H1300