

## *3138-N Merge Printer Applicator*



The Label-Aire® Model 3138-N Merge Printer Applicator prints and applies labels fast and accurately using Label-Aire's proven wipe-on labeling technology.

The advanced 3138-N Merge is Label-Aire's latest printer applicator featuring New Generation technology making it the ideal choice for the most demanding print and apply applications. The 3138-N Merge utilizes Label-Aire's wipe-on technology for fast, accurate, and versatile labeling. Advanced features include automatic setup with multiple programmable label pages for easy change-overs to labels of different sizes, rate compensation for improved label placement accuracy, and advanced user-configurable I/O connectivity. All these handy features greatly simplify setup and change-overs. The 3138-N Merge is just as tough as it is advanced. Its rugged stainless steel and anodized aluminum construction is corrosion resistant providing long-lasting durability and maintenance-free operation in the most hostile environments.

Put this advanced print and apply workhorse to work for you all day, every day. The Model 3138-N Merge Printer Applicator is built to meticulous quality standards and designed to operate reliably under the most demanding conditions.

- **Automatic setup** includes multiple programmable label pages for easy change-overs to different label sizes.
- **Wipe-on technology** is accomplished by utilizing a label loop box for the storage of pre-printed labels.
- **Automatic Speed Following (ASF)** provides accurately applied labels even through changes in product speed.
- **Digital display** for remote operator control capability.
- **Flash memory** allows easy download of system software updates.
- **Advanced I/O** is user-configurable for system output signals.

## Specs

- **Dimensions:** Height: 33.3" (846 mm), Length: 33.3" (846 mm), Width: 28.6" (726 mm)
- **Weight:** 165 lbs. (75 kg)
- **Standard Label Dimensions:** Label Width: Up to 7.2" (183 mm), Label Length: Up to 7" (178 mm) (Printer dependent)
- **Dispense Speed:** Up to 25" (635 mm) per second when label storage box is full (depending on printer and label size), up to 16" (406 mm) per second when label storage box is low (depending on printer and label size)
- **Label Dispense Accuracy:** Up to +/- 1/32" (0.8 mm)
- **Electrical:** 115 Volts AC 60 Hz 3 Amps., 220 Volts AC 50 Hz optional
- **Options:** Most O.E.M. print engines