

Fully Automatic Sleeve Shrink Packaging Machine QSJ-5040A + BSE6040



QSJ-5040A is suitable for wrapping products such as pop-cans, bottles, etc, with bottom-tray or without bottom-tray, working with BSE-6040 or other PE shrink tunnels.

Characteristic:

- The Machine adopts the advanced touch screen system for man-machine conversation, 'Schneider' programmable logic controller (PLC), 'AirTAC' air-jar, and all the rest parts adopt international famous brand.
- Up and down magnetic switch prevent sealing mistakes, and protect the operators.
- 'Schneider' PLC, 'Schneider' AC contractor, and Intelligent temperature controller performs stable.
- Large power conveyer motor, with stepless speed regulating, ensures smooth feeding.
- Up and down large power fan system ensures the excellent effect of shrinking in one time.
- Super cooling system cools the packing and makes the figuration perfectly.

Specification:

Model	QSJ-5040A	Model	BSE6040
Voltage	220V, 50-60HZ	Power supply	3phase 380V 50HZ
Power	3KW	Heater power	27KW Adjuster
Capacity	0 - 10pcs/minute	Conveyer speed	0-10m/minute
Working air pressure	4 - 6kg/cm ²	Tunnel size	1800*600*400mm
Width/thickness of the film	Max.590mm/0.03-0.25mm	Conveyer loading	25KGS MAX.
Max. packing dimension	500*300*400mm	Machinesize(L*W*H)	2800*880*1570mm
Min. packing dimension	250*50*100mm	Machine weight	285KGS
Machine size(L*W*H)	1,060*1,600*1,930mm	Shrink film	PE,POF,PVC,PP
Machine weight	400KG	Machine weight	300KG