

Internal Circulation Heat Shrink Packaging Machine BSN4020CK



Machine modeling handsome, stable quality, safe and energy saving, patented products, the first national, suitable for PVC PP POF film shrink packaging perfect effect.

Technical features:

1. Appearance and knot in accordance with national standards, the fuselage with fingerprint-resistant production after the spray.
2. Control panel using programming system, 12V DC input, key switch, digital display.
3. Conveyor using 24V DC gear motor, speed control using frequency conversion technology 0-9 file adjustment.
4. Conveyor belt with wire mesh belt, chain roller, Teflon mesh with three.
5. Heating with 220V 600W far infrared quartz heating tube.
6. Temperature control using high-precision intelligent temperature controller system, the upper and lower temperature independent adjustment.
7. Hot air circulation using 220V 60W 2200 long axis motor equipped with wind wheel.
8. Tripod detachable, tripod height adjustable.
9. Extended packaging effect is more perfect, more efficient energy.

MODE	BSN4020C	BSN5030
Voltage	380V50-60Hz	380V/50-60Hz
Power	9KW	11KW
Capacity	0-15m/min	0-15m/min
Tunnel Size	1200×400×200mm	1200×500×300mm
Product size	350×150mm	450×250mm
Transport material	Mesh belt, chain roll, Teflon	Mesh belt, chain roll, Teflon
Conveying load	20kg Max.	20kg Max.
External Dimensions	1600×560×660mm	1600×660×760mm
weight	80kg	90kg
Applicable shrinkage film	PE, POF, PVC, PP	PE, POF, PVC, PP