

Automatic Stick Liquid Packing Machine HY-YBY50



It is suitable for automatic packaging of liquid paste products in daily chemical, food, health care and pharmaceutical industries, such as: mouthwash; energy drink, energy jelly, energy supplement, etc.; syrup, red ginseng drink, grain health cream, etc.

Features

1. Adopt German Siemens PLC controller, color touch screen operation, Taiwan AIRTAC cylinder; France Schneider switching power supply.
2. Full pneumatic control, simple operation, less wear parts in the later stage, reducing parts replacement.
3. Material: The contact part of the box and material is made of SUS304 stainless steel, which meets GMP production standards.
4. The heat-generating parts and moving parts are hidden in the protective cover, which is safe and reliable.
5. The equipment is equipped with casters for easy handling and movement.

Characteristics:

1. Long strip design, the capacity can be large or small, by setting the bag length value, can achieve different weight, reduce mold replacement;
2. Rounded shaped sachet, can design the size of the nozzle, tear horizontally to prevent the material from spilling; the arc corner can also prevent children from scratching eye corners, increasing product safety.
3. Increase the vibration device to prevent the dust accumulation molding device from falling into the material feeding port, affecting the filling accuracy of the machine; at the same time, seal the material feeding hole through the food grade silica gel sheet to reduce the dust.
4. Punching die adopts HKS-9 material, after six processing techniques, high durability and long service life.
5. The equipment is easy to operate, and one ordinary female worker can see 3 sets of equipment.

Specification:

| Model | HY-YBY50 |
|-------------------------------|--|
| Filling Range | 1-100ml |
| Sachet Size | W: 25-100mm, L: 30-180mm |
| Max. Film Width | 220mm |
| Sachet Type | Round corner sitck |
| Filling Method | Pump |
| Capacity | 20-45ppm |
| Power Voltage and Consumption | 220V50-60HZ/2.0KW |
| Air Pressure and Consumption | 0.3m ³ /min 0.6-0.8Mpa |
| Dimension (L*W*H) | 670*850*1655mm |
| Weight | 300KG |
| Packaging Film Materials | PE laminated film, such as PET/AL/PE, PET/PE, Nylon/PE, etc. |
| | Thickness: 0.08~0.12mm (3 or 4 layers) |
| | Inner Core Diameter: 75mm |
| | Outer Roll Diameter: 300mm |