



ZX-AA Pouch Filling and Capping Machine



1. The machine is clean and bright, and is made by stainless steel except rack part reach to the existing standard of food industry.
2. Electric and pneumatic combined driving are used, resulting in stable driving. Filling, downward-capping and cap-screwing are fully automatic in order to save man power and reduce cost.
3. High efficiency, several pouch bags can be filled, downward-capping and cap-screwing at the same time in the machine.
4. Revision device of photoelectric sensors are installed in the machine. If cap jam in the machine, it can timely alert operator to inspect and adjust the equipment in order to avoid waste.
5. According to customer demand, we can add or decrease auto bag feeding device, auto cap vibrating device, cover, PLC and touch screen.

Technical parameters:

机型Model	ZX—1型	ZX—2型	ZX—3型	ZX—4型	ZX—6型	ZX—10型
参数Parameter						
包装速度(袋/小时) speed(cup/h)	600-1200	1200-2400	2000-3600	3000-5500	5000-7200	7200—12000
充填容量(ml) filling volume	≤5000	≤2500	≤1500	≤500	≤300	≤250
使用电源 power used	380v/50Hz					
调速方式 Speed adjustment mode	变频调速 frequency control of motor speed					
耗气量(m ³ /min) air consumption	0.6	0.6	0.55	0.70	0.6	0.75
整机功率(KW) power	3.8	3.8	3.8	3.8	5	6