

Vertical Form Fill Seal Machine ZVF-260A4



This machine integrates bag-making, filling, sealing, printing, punching and counting into one. It adopts servomotor for film pulling with timing belt and has automatic meander correction function. PLC control apparatuses all adopt international famous brand products with reliable performance. Both transverse and longitudinal seal mechanism adopt pneumatic system with stable and reliable action. Advanced design ensures that this machine fits different industrial sectors with very convenient adjustment, operation and maintenance during its service. It can be used with various types of automatic metering equipments at home and abroad.

Main performance and functional characteristics:

1. Use the intelligent temperature controller to ensure the accurate temperature, which can be adjusted on the touch screen.
2. Adopt the servo motor controlling for both film-dragging and horizontal sealing, with smooth operation, solid sealing, neat bag shape.
3. Use special bag former with a very vertical sealing, which can make out 4 sides square with smooth iron. After equipping with the gusseting device, it can stand up with solid angel bag profile.
4. Machine has both functions for collecting the extra side-film after cutting, and no collecting the extra side-film, the former type has very nice & flat sealing for vertical sealing, not easy to see the gap, and the latter can save the wrapping film with graceful view.
5. Adopt the convenient vertical sealing structure with shift and slight adjustment; Change various size bag formers, it can bring out different bag dimensions.
6. Equipped with safety protection, comply with firm's safety management requires;
7. Use intelligent temperature controlling machine to have accurate temperature control; ensure the artistic and neat seal;
8. Use PLC Servo System and pneumatic control system and super touch screen to form the drive control center; maximize the whole machine's control precision, reliability and intelligentized level;
9. This machine completes the whole packing procedure of measuring, loading materials, bagging, date printing, charging (exhausting) and products transporting automatically as well as counting;
10. Touch screen can store the technical parameters of various kinds of products, no need to reset while products changing;

11. Have error indicating system, helping to handle the trouble immediately;
12. Make block bags and hanging bags according to customers' different requires;
13. Both stainless steel machines and carbon steel machines;
14. Single-belt transportation, placidly and quickly, small friction, little waste;
15. Have stainless steel model and carbon steel model for choose.

Technical parameters:

Model	ZVF-260A4
Bag Type	Quad seal bag, gusseted bag
Operation Mode	Intermittent
Speed	Up to 50 bags/min
Bag Length	25-380mm
Bag Width	45-190mm
Side width	35-90mm
Reel Film Width	540mm
Film Thickness	0.04-0.12mm
Packing material outer diameter	Φ450mm
Packaging materials Inner Dia	Φ75mm
Voltage	AC 220V/ 50HZ, 1phase or per customer needs
Power Consumption	3KW
Compressed Air Requirement	0.6MPa, 0.36 M ³ / Min
Dimension	1355x1257x1601mm(L x W x H)
Weight	1000KG