

Food Industry Packaging ND-PB200L



This line mainly use cylinder pump for feeding, it suit for all kinds of paste and liquid filling, such as juice, jam, ketchup, and shampoo etc.. and quite match with most premade bag shape such as doy pack bag or zipper bag.

Features

1. Wide range of pouches: all kinds of pre-made pouches such as flat and stand-up pouches (with/without zip).
2. Easy to operate: PLC and color panel, fault indication on the panel.
3. Easy to adjust: Only needs 10 minutes to suitable for different pouches.
4. Frequency control: speed can be adjusted by frequency conversion within the range.
5. No pouch/incorrect pouch opening-no fill-no seal, machine alarm.
6. Machine alarm and stop when the inadequate air pressure.
7. Hygienic construction, the product contact parts are adopted sus304 stainless steel.
8. Imported engineering plastic bearings, no need to oil, no contamination.
9. Oil-free vacuum pump, avoid the pollution of the production environmental.
10. The machine clamp and clamp body use 304 stainless steel.

Technical Parameters

Model	ND-PB200L
Packing Speed	15-50bags/min (Depended on the product and filling weight)
Bag Size	W:100-200mm L:150-300mm
Filling Range	5-1500g
Total Power	3.85kw
Bag Types	All kinds of compound bags, such as flat bag, 3-side sealing bag, 4-side sealing bag, zipper bag, standup bag etc...
Overall Dimensions	4200*1800*2400mm