



Main Data

Output

- Max. 650 pcs/min

Size Range

- Length: 20-70 mm
 - Width: 16-30 mm
 - Height: 5-15 mm

Connected Load

- 18 kw

Utilities

- Compressed air consumption: 5 l/min
 - Compressed air pressure: 0.4-0.6 mPa
 - Consumption of cold water: 5 l/min
 - Temperature: 10-15 °C
 - Water pressure: 0.2 mPa

Wrapping Materials

- Wax paper
 - Aluminum paper

Wrapping Material Dimensions

- Reel diameter: 330 mm
 - Core diameter: 76 mm

Machine Measurements

- Length: 8500 mm
 - Width: 1600 mm
 - Height: 2100 mm

Machine Weight

- 3000 kg

Special Features

- Programmable controller, HMI and integrated control
- Automatic wrapping material splicer
- Candy rejection function at feeding belt and exist
- No candy no paper, automatic stop when candy jam appears, automatic stop when wrapping materials run out
- Servo motor driven assisted wrapping material feeding, cutting and positioned wrapping
- Servo motor driven candy feeding belt, automatic candy sequencing system and mechanical driven candy pusher
- Pneumatic driven cutter lifting
- Pneumatic wrapping material roll locking
- Automatic gluing system (optional)
- Modular design, easy to maintenance and cleaning
- CE safety authorized
- Safety grade: IP65

BZW1000+USD500 WRAPPING LINE

BZW1000+USD500 is designed for performed rectangle and ladder shaped chocolate and hard candy products in high speed envelop folding style

Chengdu SANKE Industry Co., Ltd.

Add: No.518 Baiyun Road Eastern Industrial Zone, Xindu District, Chengdu City, P.R. China / Postcode: 610500

Phone: +86 28 8396 4810 / Fax: +86 28 8396 4252

Website: www.san-ke.com / Facebook: www.facebook.com/SankePacking

We reserve the right to change any or all specifications without prior notice

