

Thermoplastic Injection Molding MSTX200A/PET



Master Packing joint with Ningbo injection company to supply customers with 10T-4000T, injection weight 45g-40000g, more than 30 kinds of specification injection mold machine. Master injection machine has energy-saving, environment-friendly, low noise, high rigidity, excellent performance, fast response, and high efficiency. With advanced servo motor and famous brand parts, Master injection machine becomes many customers' optimal choice for Injection needs.

Technical Parameter:

DESCRIPTION	MSTX200A/PET	
International size rating	200-860	200-1500
INJECTION UNIT		
Screw diameter	60	70
Screw L/D ratio	25	25
Shot volume(therretical)	706	1154
Injection weight(pet)	762	1245
Injection rate	305	461
Injection pressure	122	131
Screw speed	160	180

CLAMPING UNIT		
Clamping force	2000	2000
Open stroke	495	495
Space between tie bars(WxH)	530×530	530×530
Max. Mould height	530	530
Min.Mould height	200	200
Ejector stroke	160	160
Ejector force	99	99
Others		
Max.pump pressure	17.5	17.5
Pump motor power	18.5	30
Heating power	24.5	33
Machine dimension(L×W×H)	5.3×1.60×2.2	5.8×1.60×2.2
Oiltank cubage	250	390
Machine weight	6.4	6.9