

ATM-250 Standard Flow Wrapping Machine



Application:

- Suitable for packaging various kinds of regular objects like:
- Food: like Biscuits, Pies, Chocolates, Bread, Instant noodles, Cup Cakes, Energy bar, Ice cream bar, etc.
- Daily Appliances: Soap bar, Sponge, Tissue etc ...
- Medical Product: Medical marks, gauze, abrasive, drugs, Blood sampling device, etc...
- Stationery: ball pen, color pen, mark pen, Transparent adhesive, rulers, books, paper cards, etc..
- Different kinds of Hardware and decoration products.

Technical Characteristics:

- High folding strength, high working efficiency, simple operation and stable quality;
- It is a necessary machine with small volume and small floor area and matching Mask packing machine;
- The machine adopts Q235A and stainless steel structure, which is beautiful, firm and rust free, with high stability and low failure rate.
- The double inventors allow easy and soft cutting of the bag / bag / bag;
- Diagnosis of self-failure, clear failure display; Positioning stop function, no knife stuck and waste of packaging materials;
- High sensitivity photoelectric eye color mapping, numerical entry of cutting sealing position for additional precision;
- The alternative sealing device allows a firmer seal and reduces film loss.

Technical Parameters:

Model	ATM-250B	ATM-250D
Film width	Max.250mm	Max.250mm
Bag length	65-190mm or 120-280mm	90-220mm or 150-330mm
Bag width	30-110mm	30-110mm
Product height	Max.40mm	Max.55mm
Film roll diameter	Max.320mm	Max.320mm
Packaging rate	40-230 bag/min	40-230 bag/min
Machine Power	220V 50/60Hz 2.4KW	220V 50/60Hz 2.4KW
Machine size	(L)3770x(W)680x(H)1420mm	(L)3770x(W)680x(H)1420mm
Machine weight	About 500kgs	About 500kgs
Packing material applications	OPP, PE, PVC, OPP/CPP, OPP/PE, PET/VMPET/PE	OPP, PE, PVC, OPP/CPP, OPP/PE, PET/VMPET/PE