

## *HP-350X Fully Automatic Paper Straw Packing Machine with Auto Feeding System*



### **Features:**

1. The key parts of the machine adopt 304 stainless steel structure, which complies with food QS and pharmaceutical GMP hygiene standards.
2. The three-servo control machinery is more intelligent, and normal employees can be familiar with the operation in a short time.
3. Anti-empty bag function, realize material packaging, no material shutdown, save packaging film and improve packaging efficiency.
4. No need to adjust the position of the material directly input the bag length and the material length on the screen. The sealing material position is automatically corrected.
5. The memory function of packaging materials, realizes automatic storage of packaging parameters of multi-standard materials, and replaces packaging products without adjustment.
6. Anti-cutting function, reduce material damage, protect the knife seat from damage, to achieve the standard requirements for airtightness of packaging seals.
7. Replace the length of the packaging bag without adjusting the cutter speed, can use directly, it is convenient and simple.
8. Fault self-diagnosis function, the fault display is clear at a glance; the operator directly eliminates the fault according to the fault display and reduces the technical requirements.
9. The servo drive system is simple, the operation is simple and stable, and the maintenance is more convenient.
10. The three-servo packaging machine has powerful expansion functions and can be more easily matched with other production equipment to form an automatic production line.
11. Mature three-servo control technology, with overload protection, leakage protection, fault alarm and other safety devices to protect the safety and service life of machinery.

**Specification:**

<b>Model</b>	<b>HP-350X</b>
Film width	Max. 350 mm
Bag Length	120-280mm
Bag width	50-160mm
Product height	Max.40mm
Film roll diameter	Max . 320mm
Machine weight	600kg
Machine Size	(L)3770×(W)670×(H)1320mm
Packing speed	40-230bag/min
Power supply	220V. 50 / 60Hz. 2.4KVA