



Full-automatic Pillow Packaging Machine ZF-Z600X/Z450X



Z450X Z600X mainly used for single-roll packaging of OPP tape, double-sided tape, foam adhesive, stationery tape, etc. Products can be packaged with printed film, and the packaging speed can reach 50-150 packages per minute, and the unpacked products will be automatically filtered. If your product needs to be single-roll packaged, then this machine is your best choice.

Features:

1. With servo control (three servos), bag length can be set and cut in one step, saving time and film.
2. Control by imported PCL and touched screen, setting the parameter data much easier.
3. It can store 100 kinds of packing parameters. Self failure diagnosis, clear failure displaying.
4. It can be packed by printed film. High sensitivity photocell, digital input of cutting and sealing position for extra accuracy.
5. Positioning stop function, not adhesive to cutters and no waste of packing film.
6. Simple driving system, more reliable and more convenient maintenance.
7. The sealing blade wont work and let the tape slip if the distance is wrong between two tapes. It will keep inversion station once the blade touching the tape, it is convenient to directly operate after reboot.
8. Without packing film, it will stop working automatically. It will save time and film material to improve the operation efficiency.

Specification

| Model: | ZF-Z600X | ZF-Z450X |
|-----------------------------|--------------------|--------------------|
| Machine size L*W*H(mm): | 5350*960*1370 | 4075*960*1400 |
| Product size range W*Φ(mm): | (5-72)*(80-220) | (5-60)*(40-150) |
| Power supply: | 1P/220V/50HZ/6.5KW | 1P/220V/50HZ/4.4KW |
| Packing speed: | 50-100packs/min | 50-100packs/min |
| Net weight: | 500KG | 500KG |