

RL 720 Automatic Vertical Packing Machine



Main performance and functional characteristics:

- >Equipped with safety protection, comply with firm's safety management requires.
- >Use intelligent temperature controlling machine to have accurate temperature control; ensure the artistic and neat seal.
- >Use PLC Servo System and pneumatic control system and super touch screen to form the drive control center; maximize the whole machine's control precision, reliability and intelligent level.
- >This machine completes the whole packing procedure of measuring, loading materials, bagging, date printing, charging (exhausting) and products transporting automatically as well as counting.
- >Touch screen can store the technical parameters of various kinds of products, no need to reset while products changing.
- >Have error indicating system, helping to handle the trouble immediately.
- >Make block bags and hanging bags according to customers' different requires.
- >Single-belt transportation, placidly and quickly, small friction, little waste.
- >Have stainless steel model and carbon steel model for choose.

Selected installations:

- >Linked bags or multi-bags cutting function
- >Pothook holes punching function (circle hole and others)
- >Outlet conveyer machine
- >All kinds of automatic or half-automatic measuring transportation structure
- >Inflatable and exhaust functions
- >Compressed air system and nitrogen making machine

Usage:

>Suitable for measuring and packing anomalous lumpish and granule materials, such as candy, popped food, biscuit, roasted seeds and nuts, granulated sugar, deep-frozen food, milk powder, milk tea, amylum, sauce and so on.

Technical Parameters

Model	RL720
Bag size	(L) 150-450mm
	(W) 150-350mm
Film width	Max.720mm
Film thickness	0.04-0.10mm
Measuring range	Max.5000ml
Packing speed	10-40 bags/min
Air consumption	0.65Mpa, 0.6m ³ /min
Packing material	All laminated film such as PET/PE, PET/AL/PE, Nylon/PE, etc.; PE (confirm when order)
Power supply	220V/380V 50-60Hz
Power	4kw
Dimension	L1650 x W1400 x H2080mm
Weight	800kg