

TRC-120A Vertical Cartoning Machine



This machine is suitable for feeding and encasing of the blister plate. It consists of leaflet folding (1-4 folds) and feeding device, carton forming and feeding, batch number printing, sealing of case tongues at both ends etc. The whole encasing process is finished automatically. A hot-glue machine can be added to it.

Features:

- Adopt PLC and touch screen control system
- Speed can be adjusted by frequency inverter.
- All the electrical components adopt international well-known brand.
- Automatically stop when machine is overload.
- Automatically reject the cartons lacks of product or leaflet.
- Automatically trouble display, alarm and finished products counting.
- Stable performance, easy operation.

Main Technical Parameters

Encasing speed		30-120 boxes/min
Вох	Quality requirement	250-350g/m ²
	Dimension range (L×W×H)	(65-125)mm×(30-85)mm×(12-50)mm
Leaflet	Quality requirement	60-70g/m²
	Unfolded leaflet specification	(80-250)mm×(90-170)mm
	Fold range	【1-4】Fold
Compressed air	Working pressure	≥0.6Mpa
	Air consumption	120-160L/min
Power supply		220V 50Hz
Motor power		0.75kw
Machine dimension (L×W×H)		1380mm×1140mm×1800mm
Machine weight		1000kg