



YL-60 Automatic Cartoning Machine



YL-60 Automatic Cartoning Machine was finished running by a series of photo-electro controllers to make the machine stable and guarantee the packing quality. It includes cartons opening and forming, products insert into cartons, printing batch numbers, sealing, or option hot-glue device. The machine can be single-used or linked with VFFS Machine, Shrink Machine, Overwrapping Machine, and pillow packing machine to form a production line.

Feature

- Machine running without pressing if no products or incorrect position of products. And stopping automatically if incorrect position of product into carton after return or no cartons
- International famous brand of electrical component such as PLC touch screen, frequency inverters, etc.
- Automatically displaying device for trouble, speed and finished products counting.
- Automatic detection and rejection device for lacking product.
- Protecting automatically for overloading.
- Adopt human-machine operation system.
- stable performance operation is easy.
- No products no suction carton

Technical parameters

Encasing speed		30-60 boxes/min
Box	Quality requirement	250-350g/m ²
	Dimension range(L×W×H)	(70-250)mm×(80-180)mm×(20-90)mm
Compressed air	Working pressure	≥0.6mpa
	Air consumption	20m ³ /h
Power		380V/50Hz
Motor power		1.5kw
Machine dimension(L×W×H)		3800mm×1350mm×1900mm
Machine weight		1600kg